



INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation and Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein together with the Statement of inventorship and of right to grant of a Patent (Form 7/77), which was subsequently filed.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed 

Dated 29 May 2003

29 JUL 2002

NEWPORT

The
Patent
Office

1/77

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road
Newport
Gwent NP9 1RH

1.	Your reference	P3318.A4/ADS		
2.	Patent application number	29 JUL 2002		
		29 JUL 02 E736616-2 D01070 P01/7700 0.00-0217422.5		
3.	Address and postcode of the or of each applicant (<u>underline all surnames</u>)	Visteon Global Technologies, Inc. Suite 728, Parklane Towers East One Parklane Boulevard Dearborn, MI 48126-2490 United States of America		
	Patents ADP number (<i>if you know it</i>)	7940307001		
	If the applicant is a corporate body, give the country/state of its incorporation	United States of America, State of Michigan		
4.	Title of the invention	Open Loop Fuel Controller		
5.	Name of your agent (<i>if you have one</i>)	DUMMETT COPP		
	"Address for service" in the United Kingdom to which all correspondence should be sent (<i>including the postcode</i>)	25 THE SQUARE MARTLESHAM HEATH IPSWICH IP5 3SL		
	Patents ADP number (<i>if you know it</i>)	6379001		
6.	If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (<i>if you know it</i>) the or each application number	Country	Priority application number (<i>if you know it</i>)	Date of filing (<i>day / month / year</i>)
7.	If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application	Number of earlier application	Date of filing (<i>day / month / year</i>)	
8.	Is a statement of inventorship and of right to grant of a patent required in support of this request? (<i>Answer 'Yes' if:</i> a) any applicant named in part 3 is not an inventor, or b) there is an inventor who is not named as an applicant, or c) any named applicant is a corporate body. See note (d))	YES		

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description	13
Claim(s)	4
Abstract	1
Drawing(s)	5

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translation of priority documents

Statement of inventorship and right to grant of a patent (*Patents Form 7/77*) TWO

Request for preliminary examination and search (*Patents Form 9/77*) ONE

Request for substantive examination (*Patents Form 10/77*) ONE

Any other documents
(please specify)

11. I/We request the grant of a patent on the basis of this application.

Dummett Copp

Signature

Date

DUMMETT COPP

26 July 2002

12. Name and daytime telephone number of person to contact in the United Kingdom
Alison Simons
01473 660600

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.*
- Write your answers in capital letters using black ink or you may type them.*
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.*
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.*
- Once you have filled in the form you must remember to sign and date it.*
- For details of the fee and ways to pay please contact the Patent Office.*

THE PATENT OFFICE
D
29 JUL 2002

The
Patent
Office

7/77

Statement of inventorship and of
right to grant of a patent


The Patent Office

Cardiff Road
Newport
Gwent NP9 1RH

1.	Your reference	P3318.A4/ADS
2.	Patent application number	0217422.5
3.	Name of the or of each applicant	Visteon Global Technologies, Inc.
4.	Title of the invention	Open Loop Fuel Controller
5.	State how the applicant(s) derived the right from the inventor(s) to be granted a patent	BY VIRTUE OF THE EMPLOYMENT OF THE INVENTOR(S) BY VISTEON UK LIMITED AND BY VIRTUE OF AN AGREEMENT BETWEEN VISTEON UK LIMITED AND VISTEON GLOBAL TECHNOLOGIES, INC. DATED 28.6.00.
6.	How many, if any, additional Patents Forms 7/77 are attached to this form (see note (c))	ONE
7.	<p>I/We believe that the person(s) named over the page (and on any extra copies of this form) is/are the inventor(s) of the invention which the above patent application relates to.</p> <p><i>Dummett Copp</i> Signature Date</p> <p>DUMMETT COPP 26 July 2002</p>	
8.	Name and daytime telephone number of person to contact in the United Kingdom	Alison Simons 01473 660600

Notes

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there are more than three inventors, please write the names and addresses of the other inventors on the back of another Patents Form 7/77 and attach it to this form.
- d) When an application does not declare any priority, or declares priority from an earlier UK application, you must provide enough copies of this form so that the Patent Office can send one to each inventor who is not an applicant.
- e) Once you have filled in the form you must remember to sign and date it.



Enter the full name, address and postcodes of the inventors in the boxes and underline the surnames

Mark Paul Guerrier
21 Bader Walk
Northfleet
Gravesend
Kent, DA11 8PU
United Kingdom

8434391001

Patents ADP number (if you know it):

Patents ADP number (if you know it):

Reminder

Have you signed the form?

Patents ADP number (if you know it):

OPEN LOOP FUEL CONTROLLER

This invention relates to a method and apparatus for controlling the air-fuel ratio demanded by a fuel controller in order to maintain optimum performance of a catalytic converter where there is no feed back between the achieved air fuel ratio and the desired air fuel ratio.

Three way catalytic converters are used to reduce exhaust emission of nitrous oxides (NO_x) hydrocarbon (HC) and carbon monoxide (CO). In a steady state of operation the performance of the catalyst in removing these pollutants is at an optimum level when the air fuel ratio of the exhaust gas is within a narrow range, close to the stoichiometric air-fuel ratio.

Conventionally, a fuel controller is used to control the air fuel ratio demand from an engine based on feedback from an air fuel ratio sensor upstream of a catalytic converter in the exhaust passage or from two air fuel ratio sensors, one upstream of the catalytic converter, and one downstream of the catalytic converter. Operation based on such feedback is known as 'closed-loop' operation.

However, when it is desired to operate the engine away from the stoichiometric, as the air fuel sensors are insensitive to changes in the air fuel ratio other than around the stoichiometric air fuel ratio, there is no feed back correction relating to the air-fuel ratio actually achieved. Such operation is known as 'open-loop' operation.

For example, after throttle opening it may be desirable to operate on the rich side of a stoichiometric air fuel ratio

in order to provide extra torque. Another example is after deceleration fuel shut off it may be desirable to operate on the rich side of a stoichiometric air fuel ratio in order to regenerate the catalyst.

5

The problem therefore is that when an engine is operating away from stoichiometric it is in open loop operation and any error between the requested air fuel ratio and the achieved air fuel ratio is not corrected.

10

The object of this invention is to provide a method and apparatus for correcting air fuel ratio errors when in open-loop operation when the engine is operating with a substantially different air fuel ratio to that which is stoichiometric.

15

According to the present invention there is provided an open loop air fuel ratio controller comprising a detector arranged down stream of a catalyst for detecting rich breakthrough; a catalyst model having an estimator for estimating a stored oxygen level in the catalyst; a comparator for comparing an estimated stored oxygen level with a plurality of predetermined thresholds; demand adjusting means for adjusting an air fuel ratio demand in dependence upon a received signal from said comparator and upon a received signal from said detector.

20

25

This provide means for adjusting the air fuel ratio by using the estimated stored oxygen level as well as an indication of whether rich breakthrough has yet occurred.

30

It is an advantage of the controller further comprises model

adjusting means for adjusting the model in dependence upon a received signal from said comparator and upon a received signal from said detector so that the model may also be adjusted, for example if characteristics of the catalyst
5 change due to ageing.

If the comparator is arranged to compare an estimated stored oxygen level with a plurality of thresholds when the detector
10 detects rich breakthrough then different actions may be taken in dependence upon the estimated stored oxygen level falling within various ranges when rich breakthrough is detected.

Preferably either the model is adjusted or the air fuel ratio
15 demand is adjusted in particular circumstances, but not both. Therefore preferably the controller is arranged such that when the model adjusting means adjusts the model the demand adjusting means does not adjust the air fuel ratio demand. Furthermore, the controller is arranged such that when the
20 demand adjusting means adjusts the air fuel ratio demand the model adjusting means does not adjust the model.

In a preferred embodiment the model adjusting means is arranged to adjust the model to reduce or increase a maximum
25 oxygen storage value and the detector is a heated exhaust gas oxygen sensor.

According to another aspect of the invention there is also provided a method of open loop fuel control comprising the
30 steps of detecting rich breakthrough downstream of a catalyst; estimating an oxygen storage level in the catalyst; comparing the estimated oxygen storage level with a plurality

of predetermined thresholds; and adjusting the air fuel ratio demand in dependence upon the results of said comparing step and said detecting step.

- 5 It is an advantage if the method further comprises the step of adjusting the model in dependence upon the results of said comparing step and said detecting step.

10 Preferably, if the estimated oxygen storage level is less than a first predetermined threshold then the air fuel ratio demand is adjusted in a rich direction.

15 In a preferred embodiment there is a range of values within which the estimated oxygen storage level is expected to fall when a rich breakthrough is detected, and therefore not action is taken. Accordingly in this embodiment the model adjusting step and the air fuel ratio demand adjusting step are not performed if a rich breakthrough is detected and if the estimated oxygen level is greater than a second
20 predetermined threshold and less than a third predetermined threshold.

25 Preferably adjusting the air fuel ratio demand comprises the sub step of determining whether the estimated oxygen storage level is greater than a fourth predetermined threshold when a rich breakthrough is detected, if so then the air fuel ratio demand is adjusted in a lean direction.

30 Preferably the model adjusting step is arranged to adjust the model such that a maximum value for the oxygen storage level is increased if a rich breakthrough is detected and if the estimated oxygen level is between the first predetermined

threshold and the second predetermined threshold.

It follows that, preferably the model adjusting step is also arranged to adjust the model such that a maximum value for
5 the oxygen storage level is decreased if a rich breakthrough is detected and if the estimated oxygen level between the third predetermined threshold and the fourth predetermined threshold.

10 Embodiments of the invention will now be described, by way of example only, with reference to the accompanying drawings, in which

Figure 1 is a block diagram illustrating use of a
15 catalyst observer model;

Figure 2 is a graph showing the difference in operation between a new catalyst, and one which has deteriorated;

Figure 3 is a graph showing how catalyst characteristics change with age of the catalyst;

20 Figure 4 illustrates a range of estimated oxygen storage values with predetermined thresholds indicated therein; and

Figure 5 is a flow chart showing the method steps carried out in an open loop fuel controller of the present
25 invention.

Referring now to Figure 1, a model 1 of a catalyst 2 will be described. An air flow sensor 4 mounted in an intake pipe of
30 an engine 3 is used to measure air mass flow induced by the engine 3. In other embodiments of the invention the air mass flow may be estimated from other parameters, for example

manifold pressure, engine speed and air temperature.

Exhaust gases from the engine 3 are fed to the catalyst 2 mounted in an exhaust pipe. A sensor 7 measures the air fuel ratio downstream of the catalyst 2. The sensor 7 may be a Universal Exhaust Gas Oxygen (UEGO) sensor or may be a Heated Exhaust Gas Oxygen (HEGO) sensor. A HEGO sensor senses whether the air-fuel ratio is rich or lean of stoichiometric, whereas a UEGO sensor provides a measurement of the air fuel ratio. A sensor 8 measures the temperature of the catalyst 2. The catalyst 2 does not perform well at low temperatures so the model 1 has the measured catalyst temperature as an input, and does not operate until the temperature of the catalyst reaches a minimum temperature. In other embodiments the catalyst temperature may be estimated using a catalyst model.

The observer model 1 operates as will now be described, although the invention is not limited to use of this particular model, and simpler or more complex catalyst models could be utilised.

Oxygen storage of the catalyst is represented by an oxygen storage variable ϕ which is equal to zero when the catalyst is in a neutral state, is negative if the catalyst is depleted of oxygen and is positive if the catalyst is oxygen rich. It is possible to measure the air fuel ratio upstream of the catalyst 2 by use of a UEGO. However, use of a UEGO is costly, and even a UEGO has a limited range around stoichiometric within which the air fuel ratio measurement is accurate. Therefore the model used assumes that the

precatalyst air fuel ratio λ_{precat} is equal to the air fuel ratio demanded by a control system (not shown). Therefore the model 1 has as an input an air fuel ratio demand which is received from the control system.

5

The rate of change of the oxygen storage variable ϕ is estimated according to the following equation.

$$d\phi/dt = (\Delta\lambda_{\text{precat}} - N(\phi)S_{\text{wv}}) * \text{oxygen_mass}/\lambda_{\text{precat}}$$

10

$\Delta\lambda_{\text{precat}}$ is equal to $\lambda_{\text{precat}} - 1$, therefore $\Delta\lambda_{\text{precat}}$ is negative if the air fuel ratio is rich of stoichiometric, and $\Delta\lambda_{\text{precat}}$ is positive if the air fuel ratio is lean of stoichiometric. The air mass flow measured at the sensor 4 is multiplied by a constant value 0.21 which is equal to the fraction of air by mass which is oxygen, this fraction is denoted oxygen_mass in the above equation.

15

$N(\phi) = \sum a_i \phi^i$ and represents the resistance to oxygen storage of the catalyst for a particular value of ϕ as illustrated in Figure 2.

20

S_{wv} is equal to 0 when $\Delta\lambda_{\text{precat}}$ is negative i.e. the air fuel ratio is rich of stoichiometric and ϕ is greater than 0 i.e. there is excess oxygen stored in the catalyst.

25

It will be understood that when a rich air fuel ratio is supplied to the engine 3, and when there is excess oxygen stored in the catalyst 2, then the engine 3 emits gaseous components which can be oxidised by the catalyst 2, and in this case S_{wv} is equal to 0 so that

30

$$d\phi/dt = \Delta\lambda_{\text{precat}} * \text{oxygen_mass}/\lambda_{\text{precat}}$$

However, when a lean air fuel ratio is supplied to the engine
5 3 or when the catalyst 2 is depleted of oxygen then S_{wv} is
equal to 1 so that

$$d\phi/dt = (\Delta\lambda_{\text{precat}} - N(\phi)) * \text{oxygen_mass}/\lambda_{\text{precat}}$$

10 so in this case $d\phi/dt$ is reduced by an amount equal to
 $N(\phi) * \text{oxygen_mass}/\lambda_{\text{precat}}$ when compared to the previous case.

$$\text{Est}(\lambda_{\text{postcat}}) = N(\phi) S_{wv} + 1.$$

15 λ_{postcat} is the downstream air fuel ratio divided by the
stoichiometric air fuel ratio. ϕ is calculated by integrating
the above differential equation, and then $N(\phi)$ is calculated.
When $S_{wv} = 0$ then $\text{Est}(\lambda_{\text{postcat}}) = 1$, otherwise $\text{Est}(\lambda_{\text{postcat}}) =$
 $N(\phi) + 1$.

20

$\text{Est}(\lambda_{\text{postcat}})$ and the measured λ_{postcat} may be compared if the
sensor 7 is a UEGO, and the difference between them may be
used to update the coefficients a_i of the oxygen storage
characteristic curve $N(\phi)$ and the ϕ value itself so that the
25 model 1 more accurately represents the performance of the
catalyst 2. The coefficients a_i may be updated using a Kalman
filter, a description of which may be found in "Applied
Optimal Estimation", Gelb, the MIT press 1974. If the sensor
7 is a HEGO then it is only possible to determine whether
30 λ_{postcat} is rich or lean of stoichiometric, and hence it is

only possible to decide whether to increase or reduce the maximum level of ϕ , which may be regarded as the oxygen saturation level.

- 5 Figure 2 illustrates the differing $N(\phi)$ curves for a good catalyst compared with a deteriorated catalyst.

After the engine has been operating at a particular air fuel ratio for some time, then the oxygen stored in the catalyst
10 will stabilise at a value which depends upon the operating air-fuel ratio, thus $d\phi/dt = 0$ and

$$\Delta\lambda_{\text{precat}} = \Delta\lambda_{\text{postcat}}$$

Figure 3 illustrates an example oxygen storage characteristic
15 curve showing the oxygen storage value when $\Delta\lambda_{\text{precat}} = \Delta\lambda_{\text{postcat}} = 0.1$ and when $\Delta\lambda_{\text{precat}} = \Delta\lambda_{\text{postcat}} = -0.1$. Figure 3 illustrates how an oxygen storage characteristic curve may change for a deteriorated catalyst. The difference in the steady state oxygen storage value is illustrated for $\Delta\lambda_{\text{precat}} = \Delta\lambda_{\text{postcat}} = -$
20 0.1 for two examples of oxygen storage characteristic curves. Hence it will be appreciated that if fuel control is implemented using air fuel ratio thresholds measured at the sensor 7, then as the catalyst deteriorates, the fuel control scheme will allow breakthrough of NO_x when the catalyst
25 resists absorption of any more oxygen, and breakthrough of HC and CO when the catalyst is depleted of oxygen.

It is known to update a catalyst model by detecting unexpected breakthroughs. In particular the model parameters
30 are adjusted such that the maximum level of oxygen storage is adjusted to accommodate aging properties of the catalyst.

However, unexpected breakthrough may also occur when λ_{precat} does not accurately reflect lambda-demand. As explained earlier, use of a wide ranging precatalyst UEGO is not practical so adjusting the lambda demand using feedback is not possible. This invention addresses the problem of open loop fuel control together with updating of a catalyst model as the catalyst characteristics change.

10 The catalyst characteristics are only likely to change slowly over time, therefore any difference between $\text{Est}(\lambda_{\text{postcat}})$ and the measured λ_{postcat} due to catalyst ageing is likely to be within a small range. In this invention it is assumed that differences within a small range are due to catalyst aging and that larger differences are due to errors in the open loop control (i.e. due to differences between lambda-demand and λ_{precat}). The difference between $\text{Est}(\lambda_{\text{postcat}})$ and the measured λ_{postcat} is estimated by monitoring ϕ as predicted by the model 1 and detecting rich breakthrough using the sensor 7.

If the catalyst is in a neutral state then we expect ϕ to be equal to 0. If ϕ is less than 0 then we expect rich breakthrough to occur and if ϕ is greater than 0 then we do not expect rich breakthrough to occur (although lean breakthrough might then occur resulting in NO_x emissions)

However, to allow for some tolerance a range may be defined, within which is it expected that ϕ will fall when rich breakthrough occurs. Figure 4 illustrates a range of ϕ values with

predetermined thresholds A, B, C and D indicated therein.

When rich breakthrough is detected the current value of ϕ estimated by the model 1 is used to determine what if any action is to be taken. A first predetermined threshold D is defined, and if ϕ falls below this threshold then rich breakthrough is considered to have occurred very late and the open loop fuel control is adjusted accordingly. A second predetermined threshold C is defined and if ϕ is between the first predetermined threshold D and the second predetermined threshold C then rich breakthrough is considered to have occurred late enough for the model to need to be updated. A third predetermined threshold B is defined and if ϕ falls between the second predetermined threshold C and the third predetermined threshold B when rich breakthrough occurs then this is considered to be within normal limits. Finally a fourth predetermined threshold A is defined and if ϕ is between the third predetermined threshold B and the fourth predetermined threshold A then rich break through is considered to have occurred early enough for the model to need to be updated. If ϕ is greater than the fourth predetermined threshold A then it is considered that rich breakthrough has occurred very early and the open loop fuel control is adjusted accordingly. $D \leq C \leq B \leq A$, and Figure 4 indicates the conclusion made when ϕ falls within the ranges shown. It will be appreciated that $C \leq 0 \leq B$ so that rich breakthrough is expected to occur close to $\phi = 0$. Also it is with noting that one or more thresholds may be equal to one another, so for example the tolerance range C-B could be set to be equal to 0. Finally it is worth noting that if no rich break through is detected and ϕ is less than the first

predetermined threshold D then rich breakthrough is considered to have occurred very late and the open loop fuel control is adjusted accordingly.

- 5 Figure 5 illustrates the steps taken by an open loop fuel controller according to one embodiment of the present invention.

If rich breakthrough is detected at the sensor 7 at step 40,
10 then ϕ is compared to the first predetermined threshold D at step 42. If ϕ is less than D then rich breakthrough has occurred very much later than the model 1 predicts. Therefore it is assumed that the error is due to a difference between the lambda demand and the achieved lambda (i.e. λ_{precat}). In
15 this case at step 44 the lambda demand is adjusted to become richer. If ϕ is not less than D at step 42 then ϕ is compared to the second predetermined threshold C at step 46. If ϕ is less than C it is assumed that the error is due to a change in the catalyst characteristics and the catalyst model is
20 adjusted so that the saturation level is increased at step 48.

If ϕ is not less than C at step 46 then ϕ is compared to the third predetermined threshold B at step 50. If ϕ is less than
25 B it is considered that rich break trough has occurred within expected range of ϕ and no action is taken. However, if ϕ is not less than B at step 50 then ϕ is compared to the first predetermined threshold A at step 52.

30 If ϕ is less than A it is assumed that the error is due to a

change in the catalyst characteristics and the catalyst model is adjusted so that the saturation level is decreased at step 54.

5 If ϕ is not less than A then rich breakthrough has occurred very much earlier than the model 1 predicts. Therefore it is assumed that the error is due to a difference between the lambda demand and the achieved lambda (i.e. λ_{precat}). In this case at step 56 the lambda demand is adjusted to become
10 leaner.

Lambda demand may be adjusted by means of a data table, which is updated according to the value of ϕ at step 56 or 44 as appropriate, and which is added to the lambda demand as
15 determined by a conventional open loop fuel controller.

If rich breakthrough is not detected at step 40, then at step 58 ϕ is compared to the first predetermined threshold D. If ϕ is less than D then rich breakthrough has occurred very much
20 later than the model 1 predicts. Therefore it is assumed that the error is due to a difference between the lambda demand and the achieved lambda (i.e. λ_{precat}). In this case at step 44 the lambda demand is adjusted to become richer.

25 It is intended that the foregoing detailed description be regarded as illustrative rather than limiting and that it be understood that it is the following claims, which are intended to define the scope of the invention.

30

CLAIMS

1. An open loop air fuel ratio controller comprising
a detector arranged down stream of a catalyst for
5 detecting rich breakthrough;
a catalyst model having an estimator for estimating a
stored oxygen level in the catalyst;
a comparator for comparing an estimated stored oxygen
level with a plurality of predetermined thresholds;
10 demand adjusting means for adjusting an air fuel ratio
demand in dependence upon a received signal from said
comparator and upon a received signal from said
detector.
- 15 2. An open loop air fuel ratio controller according to
claim 1, further comprising
model adjusting means for adjusting the model in
dependence upon a received signal from said comparator
and upon a received signal from said detector.
20
3. An open loop air fuel ratio controller according to
claim 1 or claim 2, in which the comparator is arranged to
compare an estimated stored oxygen level with a plurality of
25 thresholds when the detector detects rich breakthrough.
4. An open loop air fuel ratio controller according to
claim 3, in which the controller is arranged such that when
the model adjusting means adjusts the model the demand
30 adjusting means does not adjust the air fuel ratio demand.
5. An open loop air fuel ratio controller according to

claim 4, in which the controller is arranged such that when the demand adjusting means adjusts the air fuel ratio demand the model adjusting means does not adjust the model.

- 5 6. An open loop air fuel ratio controller according to any one of the preceding claims in which the model adjusting means is arranged to adjust the model to reduce or increase a maximum oxygen storage value.
- 10 7. An open loop air fuel ratio controller according to any one of the preceding claims in which the detector is a heated exhaust gas oxygen sensor.
- 15 8. A method of open loop fuel control comprising the steps of
 detecting rich breakthrough downstream of a catalyst;
 estimating an oxygen storage level in the catalyst;
 comparing the estimated oxygen storage level with a plurality of predetermined thresholds; and
20 adjusting the air fuel ratio demand in dependence upon the results of said comparing step and said detecting step.
- 25 9. A method of open loop fuel control according to claim 8, further comprising the step of
 adjusting the model in dependence upon the results of said comparing step and said detecting step.
- 30 10. A method according to claim 8 or claim 9, in which adjusting the air fuel ratio demand comprises the sub step of
 if the estimated oxygen storage level is less than a first predetermined threshold then the air fuel ratio demand is adjusted in a rich direction.

11. A method according to any one of claim 8 to 10, in which the model adjusting step and the air fuel ratio demand
5 adjusting step are not performed if a rich breakthrough is detected and if the estimated oxygen level is greater than a second predetermined threshold and less than a third predetermined threshold.
- 10 12. A method according to any one of claim 8 to 11, in which adjusting the air fuel ratio demand comprises the sub step of
if a rich breakthrough is detected and the
estimated oxygen storage level is greater than a fourth
predetermined threshold then the air fuel ratio demand is
15 adjusted in a lean direction.
13. A method according to any one of claims 8 to 12, in which the model adjusting step is arranged to adjust the model such that a maximum value for the oxygen storage level
20 is increased if a rich breakthrough is detected and if the estimated oxygen level is greater than the first predetermined threshold and less than the second predetermined threshold.
- 25 14. A method according to any one of claims 8 to 12, in which the model adjusting step is arranged to adjust the model such that a maximum value for the oxygen storage level is decreased if a rich breakthrough is detected and if the estimated oxygen level is greater than the third
30 predetermined threshold and less than the fourth predetermined threshold.

15. A method according to any one of claims 11 to 14 wherein
the first predetermined threshold is less than or equal to
the second predetermined threshold and the second
predetermined threshold is less than or equal to the third
5 predetermined threshold.

16. A method according to any one of claims 12 to 14 wherein
the first predetermined threshold is less than or equal to
the second predetermined threshold and the second
10 predetermined threshold is less than or equal to the third
predetermined threshold and the third predetermined threshold
is less than or equal to the fourth predetermined threshold.

17. An air fuel ratio controller substantially as herein
15 described, with reference to the accompanying drawings.

18. A method of open loop fuel control substantially as
herein described with reference to the accompanying drawings.

20

25

ABSTRACT
OPEN LOOP FUEL CONTROLLER

This invention relates to a method and apparatus for
5 controlling the air-fuel ratio demanded by a fuel controller
in order to maintain optimum performance of a catalytic
converter. The invention provides an open loop fuel
controller comprising a detector arranged down stream of a
catalyst for detecting rich breakthrough; a catalyst model
10 having an estimator for estimating a stored oxygen level in
the catalyst; a comparator for comparing an estimated stored
oxygen level with a plurality of predetermined thresholds;
demand adjusting means for adjusting an air fuel ratio demand
in dependence upon a received signal from said comparator and
15 upon a received signal from said detector. A method of open
loop fuel control is also provided.

Figure 5

Fig. 1






Fig. 2







Fig.3



Value of ϕ when rich break through occurs

